



## Schalldämpfer einfach silencer basic



No 1



No 2



<b>Betriebstemperatur</b>	-20°C bis +70°C	<b>operating temperature</b>	-20°C up to +70°C
<b>Betriebsdruck</b>	max. 12bar	<b>operating pressure</b>	max. 12bar
<b>Werkstoff</b>	Sinterbronze (36µm) Messing (Ms58) Edelstahl (AISI 304)	<b>material</b>	sintered bronze (36µm) brass (Ms58) stainless steel (AISI 304)
<b>Medium</b>	Druckluft	<b>medium</b>	compressed air

G	ØA [mm]	ØB [mm]	H [mm]	L1 [mm]	L2 [mm]	S [mm]	No
G1/8	8,0	11,0	5,5	21,0	15,5	1,5	1
G1/4	10,0	14,0	8,5	27,0	18,5	1,5	1
G3/8	15,0	18,0	11,0	36,0	25,0	2,0	1
G1/2	19,0	24,0	11,0	44,0	33,0	2,0	1
G1/8	8,0	12,0	6,0	21,0	15,0	-	2
G1/4	11,0	15,0	6,0	25,0	19,0	-	2
G3/8	15,0	19,0	8,0	36,0	28,0	-	2
G1/2	18,0	23,0	10,0	43,0	33,0	-	2
G3/4	23,0	30,0	13,0	53,0	40,0	-	2
G1	28,0	38,0	15,0	63,0	48,0	-	2
M5	5,0	6,0	4,5	13,0	8,5	-	2

**weitere Optionen und Zubehör auf Anfrage**  
more options and accessories on request